



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Device application	Lightweight installation
Drilling diameter	5.5 mm brick 5.5 mm concrete
Drilling depth	>= 20 mm
Screw diameter	3.5...5 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	0.3 kN shear solid brick 4.5 0.4 kN shear concrete C25 4.5 0.15 kN pull-out load concrete C25 6 0.15 kN pull-out load solid brick 6
Practical load capacity	40 kg shear concrete 4.5 15 kg pull-out load concrete 6 30 kg shear solid brick 4.5 15 kg pull-out load solid brick 6
Colour tint	White
Ambient air temperature for operation	-50...80 °C
Diameter	5.5 mm
Length	16.5 mm

Environment

quantity per set	Set of 100
sale per indivisible quantity	10
product weight	0.0004 kg

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.