Motion detectors

IS 240 DUO

black EAN 4007841 602710

























infrared sensor 240°

max. 12 m

.

1000 W max.

IP54

0° horizontal

2000 lux

Ideal 2 m

manufacture's saving warranty steinel.de/garantie

Function description

Round the corner. Infrared wall sensor IS 240 DUO, for indoors and out, 240° angle of coverage, reach up to 12 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	90 x 60 x 100 mm
Mains power supply	230 – 240 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, Outdoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall, corner
Installation	Surface wiring
Switching zones	276 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	1,80 – 4,00 m
Optimum mounting height	2 m
Detection angle	240 °
Angle of aperture	180°
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	r = 5 m (52 m²)

Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	10 s – 15 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	^S 6 pcs.
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	No
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	black
Colour, RAL	9005
Manufacturer's Warranty	3 years
Version	black
PU1, EAN	4007841602710

Motion detectors

IS 240 DUO

black EAN 4007841 602710




Accessories

EAN 4007841 630119

Corner wall mount 01

Detection Zone



Mögliche Montagehöhe: 1,80 m - 4,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

