



T12/T14 IP67 Poultry Farm LED Light Fitting



Description

- The tube is certificated by SAA, CE, ROHS, IP67.
- Meet IEC VDE safety standard with built-in isolated driver.

Item	Material	Description
PC pipe	Full PC Pipe	Safety for waterproof
	Pure PC / 94V-0	Will not Fade
		will not burst
		Anti-weak base
Connector	Nylon+NBR for seal	Alkali, wear resistance,
		Weather resistance
		CE, IP68 Level
Waterproof End Cap	PC+Fiber	Will not Fade
		Anti-weak base
PCB board	Aluminum	Hi-pot test up to 2000V
		1.5 transmission rate

LED driver designed_Traic dimmable		
Main Components	Brand	Specification
Electrolytic Capacitance	Aishi	50,000hrs lifetime
Dimmable IC	MPS	Dimm brightness from 0.5%-100%)
MOS	Silan	SV4N65 TO-220
Transformer	China	MAX wattage is 36W

Item	Material	Description
LED chips SMD2835	10*30mil	26-28lm/pcs
	CRI	Ra80+
	Gold wire	Heraeus gold
	Bracket	copper bracket.

Product information

Product Code	Type of Driver	Type of Cable	Power	LED info	Total Length	Lumens	Remark
HT-T12POULTRY180	180-264Vac @ Dimmable	2M	28W	SMD2835 168pcs	L: 1500mm OD32mm	3080Lm Max	IP67
HT-T12POULTRY270	180-264Vac @ Dimmable	2M	28W	SMD2835 168pcs	L: 1500mm OD32mm	3080Lm Max	IP67

- 180 - 270 degree beam angle
- Flicker free
- T12
- 4,000 - 4,2000K
- 1.5 Mtr
- IK10 (20 Joules) protection against mechanical impact.

Product Code	Type of Driver	Type of Cable	Power	LED info	Total Length	Lumens	Remark
HT-T114AC25WRFD	180-264Vac @ Dimmable	2M	20W	SMD2835 168pcs	L: 1200mm OD32mm	2750Lm Max	IP67

- 360 degree beam angle
- Flicker free
- T14
- 6,000 - 6,5000K
- 1.2 Mtr
- IK10 (20 Joules) protection against mechanical impact.

