

Technical Specification



Product Code: EMDLED3WMBULK2

Description: 3W LED IP65 Maintained Emergency Bulkhead

4001200	1000 Marca 10000 Marca	
General Information	Emergency Overview	
Dimensions 345mm x 110mm x 60n	nm Emergency Operation Maintained or Non-Ma	intained
Materials Polycarbonate Housing	Status Indicator Green LED Indicator	
Mounting Ceiling or Wall	Battery Information	
Weight 0.6kg	Specification 3.6V 1200mAh Ni-Cd	
Luminaire Overview	Duration 3 Hours Emergency	
Colour Temperature 5500K	Environment	
LED Lamp Type 8 x SMD 2835	Ingress Protection IP65	
Luminaire Output	Belative Humidity	
Mains Luminous Flux 120 Lumens	Resistance Less than 90%	
Emergency Luminous Flux 100 Lumens	Operating Temperature 0°C to 40°C	
Power Operating Voltage 220 - 240V AC, 50Hz		
Accessories		
EMBAT3.6V1200SER 3.6V 1200mA	n Ni-Cd Battery	
EMBULK2FLUSH Bulkhead Flus	sh Kit	
EMBULKLGD Emergency B	ulkhead Legend	

Features

Legend Included

Escape Route 1 lux min

-		□⊷□			
Mounting Height	Axial/ Wall	Axial/ Axial	Transverse/ Axial	Transverse/ Transverse	Transverse/ Wall
2.0m	з	7	6	5.5	2
2.5m	з	8	7	6	2.5
3.0m	3.2	8.8	7.8	6.8	2.6

Illumiance values based on a maintenance factor of 0.8 Photometric spacing data 1 Lux (centre to centre in metres on emergency escape routes)

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

Page 1 of 1 Rev.1 Errors & Omissions excluded Specification is subject to change without notice