Fitting


- Point the spring clips upwards and fit the two longer arms into the ceiling hole.
- Push the unit upward until firmly in position, ensuring that the cable is not trapped.
- Push the lamp into the lampholder, and fit the lamp using the circlip.
- Replace fuse and switch on.



Fitting/replacing the bulbs

When changing a bulb, always switch off at the mains and allow the bulb to cool before handling. Dispose of used bulbs carefully. Use a soft cloth to handle bulbs, avoid directly touching the bulbs as this will shorten their life. Do not exceed the wattage stated or use a different shape bulb from that indicated on the fitting. Remove circlip by squeezing tabs together, to release the bulb. Twist the bulb to remove from the lampholder.

To refit, twist the bulb into the lampholder, fit into place. Fit the circlip into place by squeezing the tabs together and clipping into place.



50W GU10 Mains Halogen

Care and Cleaning

We recommend cleaning with a soft dry cloth. Do not use solvents or abrasive cleaners as these could damage the finish.

Recycling advice

- $\overleftarrow{\mathbb{M}}$ Waste electrical products should not be disposed of with household waste. Please recycle
- where facilities exist. Check with your Local Authority or retailer for recycling advice.

Safety information

For your safety, always switch off the supply before changing lightbulbs, or cleaning.

For more information contact: U

Unit 7/8 Ashbourne Business Centre, Ballybin Road, Ashbourne, Co. Meath, Ireland, A84 YP58 Phone: 00353 1 835 7447

Solas Geal Distribution

Unit 32 Junction One Business Park, Valley Road, Birkenhead, Merseyside, UK, CH41 7ED UK Ph: 0330 551 7000

Website: www.sgd.ie

Installation Manual

EDLCON-WH EDLCON-CH EDLCON-MC



GU10 CONVERTOR DOWNLIGHT



Thank you for purchasing this light fitting.

Please read the instructions carefully before use to ensure safe and satisfactory operation of this product. Please retain these instructions for future reference.

Warning



This product is Double Insulated and does not require connection to an Earth circuit.

Please read these instructions carefully before commencing any work.

This unit must be fitted by a competent and qualified electrician.

Install in accordance with IEE Wiring regulations and current Building Regulations.

To prevent electrocution switch off at mains supply before installing or maintaining this fitting. Ensure other persons cannot restore the electrical supply without your knowledge.

This light fitting should be connected to a fused circuit.

If replacing an existing fitting, make a careful note of the connections.

Always use the correct type and wattage bulb.

Specification

Voltage: 240V 50Hz a.c. All Models - 1 x Max. 50W GU10 Mains Halogen. Suitable for use with LED lamps. Lamp: IP rating: 20

Layout

- Plan the desired layout of these fittings carefully, ensuring the cables will reach the distances between the connector block and each light fitting.
- Avoid locating any cables in positions that would cause a hazard. Position cables and connector block away from areas where they may be at risk from being cut, trapped or damaged.
- Cables that are to be in walls must be protected using suitable conduit or plastic trunking.

Spotlights give a concentrated beam of light and must not be positioned any closer than 0.5M (50cm) to the illuminated surface.

Fixing sizes

65-130mm diameter cutout

150mm minimum cavity depth.

Never exceed the wattage stated.


When changing a bulb, always switch off at the mains and allow the old bulb to cool down before handling.

Dispose of used bulbs carefully and responsibly.

This product is suitable for dimming when used in conjunction with a dimmable lamp. Always check dimming capability of the intended lamps.

Waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your local authority or retailer for recycling advice.

Ceiling Outside Zones




Installation

- Ensure the mains is disconnected. Remove the existing fitting and discard.
- · Disconnect the wiring, and connect the chosen lampholder for mains voltage halogen **GU10**
- Fit the extended spring clips to the downlight and fit the downlight into the surround.
- Wiring

This product is double insulated and must not be earthed. If there are any incoming earth cables, they must be joined together and well insulated with good guality insulation tape. This is to ensure earth continuity throughout your property.

Having correctly identified the wiring from your existing light fitting and connect to the connection block inside the product in the following way:



- · You have correctly identified the wires.
- · The connections are tight.

 No loose strands have been left out of the connection block.

This product has no special protection against the ingress of moisture, and is rated as IP20. This product is not suitable for use in Zones 0, 1

or 2, of a bathroom. See diagram. The mains supply must be fitted to a 30mA RCD.

- · Lift the downlight into position. Feed the cable throught the centre of the downlight
- Wire as detailed below.

Check that...







EU DECLARATION OF CONFORMITY

Manufacturers Name: Solas Geal Distribution Unit 7/8 Ashbourne Business Centre, Ballybin Road, Ashbourne, Co. Meath, A84 YP58.

Declaration Number :

0020 - EDLCON

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Products: GU10 Convertor Downlight Model Number: EDLCON-WH, EDLCON-CH, EDLCON-MC

Codes		
EDLCON-WH	EDLCON-CH	EDLCON-MC

The product/model of the declaration described above is in conformity with the relevant Community harmonisation legislation:

LVD (2014/35/EU)

The product/model of the declaration described above is in conformity with the standards and technical specifications listed below:

EN 60598-2-2:2012, EN60589-1:2015+A1:2018,EN IEC55015:2019,EN61547:2009, EN IEC 61000-3-2:2019,EN 61000-3-3:2013+A1:2019





Signed:

Date:

Place of Issue: Republic of Ireland