

Technical Specification

CLICK® ScolmoreGROUP

Product Code: DPAB038BK Description: 5A Round Pin Socket Outlet





Insert: Urea

Terminals: Brass

Internal Busbars: Formed Pressed Brass

General Information

Plate Dimensions 88mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)
Plate Design & Finish Rounded Profile Antique Brass

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 5A
Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 1.2Nm

Terminal Capacity 4 x 1.5mm² or 3 x 2.5mm²

Switched No
Twin Earth Terminals No
Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 546: 1950

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621