

## **Technical Specification**



Product Code: CMA052

Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional Flex Outlet





## General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
Finish	Polar White		
Materials	Front Plate, Rocker Switch & Fuse Drawer Urea	Rear Housing: Urea	
	Neon Lens: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivate	d Contacts: Silver "on	-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Ste	
Anti Microbial Certified	Yes	1	
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Rating & Type	13A (BS 1362)		
Termination Type	Screw		
Terminal Size (mm)	Ø5 Tern	ninal Torque Value (Nm)	2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4		
Switched	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Orange
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location	Bottom of Plate Flex	Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		
Standards BS 1363			
BS 1362	-		
diagram	ure that the mains supply is isolated before commencing installation and refer to the circuit gram with the relevant product. e earth cables must always be covered with appropriate sleeving and wired to the earth terminal.		
	moulded accessories are manufactured us es to antimicrobial additives that inhibit the g		

properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



Page 1 of 1 (30/06/22) Errors & Omissions excluded. Specification is subject to change without notice.