

Technical Specification



Product Code: CMA053

Description: 13A Fused Connection Unit With Neon & Optional Flex Outlet

FUSED		Control of the second s	
General Information	tion		
Plate Dimensions (
Plate Fixing Centres - Horizontal (, , , , , , , , ,	1	
	Style Rounded Profile		
	nish Polar White		
Mate		ver: Urea Rear Housing: Urea	
	Neon Lens: Polycarbona		
	Terminal Screws: Steel &		rmed Pressed Brass
	Earth Strap: Mild Steel		
Anti Microbial Cert	ified Yes		
Rated Voltage (V~)	(Ue) 250	Frequency (Hz)	50
Resistive Load Rating			
Fuse Fitted Rating &			
Termination ⁻			
Terminal Size (,	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (n			
Swite			
Twin Earth Termi		Indianter Onlaur	0
Neon India		Indicator Colour	Orange
Product Mar Flex Outlet Avail	0		
Flex Outlet Loca		Flex Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (
Ingress Protect	,		
Operational Temperature			
Warranty (Ye			
	,		
	1363-4 1362		
Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.			

UK CA