

MNX ABS 175/100 HG



Sample photo

Order symbol: ABS 175/100 HG
Product nbr: 6081321
Description: Enclosure, ABS
Remarks: Grey cover

EAN: 6418074022981
El. number:
Finland: 3420563
Electric No. Denmark: 8212023314
Electric No. Italy: 7361115
Electric No. Sweden: 2535766

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:		
mm:	180	180	100	MIN 15	DIN-15 Mounting rail
inch:	7.1	7.1	3.9	MIV 15	DIN-35 Mounting rail
Materials:			FP A 175/180	Front plate (Aluminium)	
Material:	ABS		HFP 180	Front plate hinge series	
Base colour:	RAL 7035 -light grey		FP 22046	Wall fastening lug (4 pcs)	
Cover screws material:	Polyamide		Rating:		
Cover colour:	RAL 7035 -light grey		Ingress Protection (EN 60529): IP66/IP67		
Cover screws colour:	Grey		Impact Resistance (EN 62262): IK07		
Gasket material:	TPE		Electrical insulation: Totally insulated		
Temperatures:			Halogen free (DIN/VDE 0472, Part 815): 1		
Temperature °C (short term):	-40 ... 80 °C		Flammability Rating: UL 94 HB		
Temperature °C (continuous):	-40 ... 60 °C		Glow Wire Test (IEC 695-2-1) °C: 650		
Temperature °F (short term):	-40 ... 175 °F		NEMA Class: NEMA 1, 4, 4X, 6, 12, 13		
Temperature °F (continuous):	-40 ... 140 °F		Certificates:		
Accessories:			SGS Fimko		
MIV 175	Mounting plate (Galvanized steel)		Gost R		

