Product datasheet Characteristics

NSYS3D7525P

Spacial S3D plain door with mount.plate. H700xW500xD250.IP66 IK10 RAL7035.





Main

iviaiii		
Range	Spacial	
Product name	Spacial S3D	
Application	Multi-purpose	
Category	Compact enclosure	;
Enclosure nominal height	700 mm	;
Enclosure nominal width	500 mm	
Enclosure nominal depth	250 mm	
Door type	Plain	
Mounting plate description	Plain	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate	-

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	

Surface finish	Enclosure: epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	CUL GL LR UL DNV BV
Net weight	19 kg
Environment	
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Packing Units	
Package 1 Weight	19 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
	REACh Declaration
REACh Regulation	
<u> </u>	Yes
REACh free of SVHC	Yes Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
REACh free of SVHC EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh free of SVHC EU RoHS Directive Mercury free	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
REACh Regulation REACh free of SVHC EU RoHS Directive Mercury free RoHS exemption information China RoHS Regulation	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes

Contractual warranty

Contraction warranty		
Warranty	18 months	