

# Ei650RF

## RadioLINK+ Optical Smoke Alarm



- Optical sensor - quick response to slow smouldering fires
- 10 year Lithium battery powered
- RadioLINK Wireless interconnection
- Built in AudioLINK data extraction technology
- Kitemarked to BS EN14604:2005



### Description

The Ei650RF RadioLINK+ Optical Smoke Alarm is powered by a 10 year life sealed in Lithium cell. It is able to wirelessly interconnect with any other RadioLINK products and also features a large test button and twist on base with an anti-tamper locking option

### Technical

<b>Sensor Type</b>	Optical - with dust compensation	<b>RF Frequency (MHz)</b>	868.499
<b>RF Range (m)</b>	>100 in free air	<b>Indicators</b>	Red - Fault / Blue - RF transmission / Green - Monitoring
<b>Battery Type</b>	Lithium primary	<b>Technologies</b>	AudioLINK/RadioLINK+

### Dimensions & Weights

<b>Depth (mm)</b>	55	<b>Height (mm)</b>	125
<b>Width (mm)</b>	120	<b>Product weight (kg)</b>	0.21
<b>Packaged weight (kg)</b>	0.266		

### Approvals & Warranty

<b>Certification/Approvals</b>	VDS EN 14604:2005 / EN 300 220-1 / EN 301 489-1	<b>Warranty</b>	5 year warranty
<b>EAN Number</b>	5099383005837		

### Environmental

<b>Humidity Range (%)</b>	15-95	<b>Temperature Range (°C)</b>	-10 to 40
---------------------------	-------	-------------------------------	-----------