Product data sheet EHN111





EHN111

| Daily time switch 1 channel, | 3 modules with reserve |
|------------------------------|------------------------|
|------------------------------|------------------------|

| Technical Properties | |
|---|--------------|
| Type of programming | analog |
| Cycle | daily |
| Shortest switching time | 15 mn |
| Type of contacts | 1 changeover |
| Rated operational voltage Ue | 230 / 240 V |
| Supply failure reserve | 120 h |
| Breaking capacity | 16A 250V AC1 |
| Max. power with incandescent lamps | 900 W |
| Type of connection | with screw |
| Connection cross-sect. flexible conductor | 1 / 4mm² |
| Connection cross-sect. rigid cable | 1 / 4mm² |
| Fixing mode | Din-Rail |
| Frequency | 50/60 Hz |
| Number of channels | 1 |
| Number of program steps | 96 |
| Operating temperature | -10 55 °C |
| Storage/transport temperature | -10 55 °C |
| Protection index IP | IP20 |
| Summer / Winter time change | manual |
| Power consumption (operation) | 0,5 VA |
| Height of installed product | 90 mm |
| Width of installed product | 54 mm |
| Depth of installed product | 60 mm |
| Number of contacts | 1 |
| Number of modules | 3 |
| Working accuracy | 5 |
| Total power loss under IN | 1 W |
| Power dissipation per coil | 0,5 W |
| Charging time of the power reserve in hours | 120 |
| Supply voltage | 230V AC |