

Wallbox Pulsar Plus

Wallbox Pulsar Plus is a practical, intelligent charging system for electric vehicles and plug-in hybrids, which connects to the myWallbox charging management platform using Wi-Fi or Bluetooth. The Pulsar Plus comes with the addition of integrated DC leakage protection as standard.

Pulsar Plus is compact and features the most advanced technology to provide maximum charging performance. Pulsar Plus easily adapts to any installation, in private garages or shared parking.

Key Features

- Always connected via Wi-Fi or Bluetooth.
- Optimize your charging infrastructure and reduce charging times with Power Boost technology.
- · Integrated charging status lights.
- · Integrated DC leakage protection.
- · Compact design.

General Specifications

Electrical Specifications

Charging Power

Rated Current

Cable Width

Configurable Current

Rated Frequency

Protection Rating Surge Category

RCCB

Residual Current Detection

Rated Voltage AC ± 10%

Connector type (IEC 62196-2)

Pulsar Plus
5 m (7 m optional) ^[1]
White or Black
Mode 3
166x163x82 mm (without cable)
1 kg (without cable)
-25 °C to 40 °C
-40 °C to 70 °C
rk (LVD 2014/35/EU, EMCD 2014/30/EU) IEC 61851-1, IEC 61851-22, IEC 62196-2

7,4 kW

220 V - 240 V

Type 1/ Type 2

32 A (1P)

11 kW

400 V

16 A (3P)

Type 2

22 kW

400 V

Type 2

32 A (3P)

5 x 10 mm²

50 Hz / 60 Hz

IP54 / IK08


DC 6 mA [2]


CAT III


from 6 A to rated current

External RCCB required[3]

Dimensions











User Interface and Communications

Connectivity Wi-Fi / Bluetooth Wallbox App / myWallbox Portal User Identification User Interface Wallbox App / myWallbox Portal Halo RGB LED / Wallbox App / myWallbox Portal Charger Status Information Included Features Power Sharing Smart Optional Features Power Boost



[1] Only available for Type 2 3P 32 A chargers.
[2] Internal RDC-DD meets tripping time characteristics according to IEC 62955.

wallbox

[3] Type A or Type B according to local regulations

Part Number Structure

	XX.	X X -)	(-X-	-X->	(-XXX	-X
	1		2 3	4 E	6	7

Position	1 - MODEL	2 - CABLE	3 - CONNECTOR	4 - POWER	5 - ADDITIONAL FEATURE	6 - CUSTOM	7 - REVISION
Variants - Definition	PLP1 - Pulsar	0 - 5 m	1 - Type 1	2 - 7,4 kW 3 - 11 kW 4 - 22 kW	3 - Residual current	XX1 - White	X - Revision X
	Plus	M - 7 m	2 - Type 2		detection	XX2 - Black	X - Kevisioi i X

www.wallbox.com sales@wallbox.com

myWallbox Portal

The myWallbox cloud platform allows you to configure, monitor and remotely manage your charger, via mobile app or web portal. It is suitable for private and business use.



- Information and management in real time: Access from any device to get information about consumption, charging time, energy cost or your charger's active and uploaded sessions.
- Regular reports: Easily download all information on energy consumption, costs, uploaded sessions, historical data and much more, whenever you need it.
- Remote configuration: Set the charging current according to your needs or lock and unlock your charger to avoid misuse.
 All with a single click.

Wallbox App

Manage all your device settings from your mobile phone or tablet through the Wallbox application.

- Acts as a link between the charger and the myWallbox portal via Bluetooth.
- Set up your device and get access to your consumption.
- Program charging sessions when energy price is lower.
- Set the charging current according to your needs or lock and unlock your charger to avoid misuse. All with a single click.



www.wallbox.com sales@wallbox.com