

## DATASHEET - IS-100/3



**Main switch, 240 V, 100A, 3HP**

**Part no.** IS-100/3  
**Catalog No.** 276284  
**Alternate Catalog No.** IS-100/3  
**EL-Nummer (Norway)** 0001460856



Similar to illustration

## Delivery program

Basic function			Main load disconnecter switch
Number of poles			3 pole
Application			Switchgear for industrial and advanced commercial applications
Rated current	$I_n$	A	100
Product range			IS
Contact sequence			

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	100
Heat dissipation per pole, current-dependent	$P_{vid}$	W	3.9
Equipment heat dissipation, current-dependent	$P_{vid}$	W	11.6
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

## Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecI@ss10.0.1-27-14-23-01 [AFZ813014])			
Switching function			Other
Number of contacts as normally open contact			3
Number of contacts as normally closed contact			3
Number of contacts as change-over contact			0
Number of poles			3
Rated current		A	100
Rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	10
Short-circuit breaking capacity (I <sub>cw</sub> )		kA	2
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No
Colour calotte			
Lamp type			
Lamp socket			

Max. lamp power		W	0
Width in number of modular spacings			3
Built-in depth		mm	69.5
Degree of protection (IP)			IP40

**Dimensions**

