



Main

Range of product	Prisma Plus System G
Product or component type	Enclosure

Complementary

Installation description	Pack enclosure: 550 mm
[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 60439-1
[Ie] rated operational current	160 A at 40 °C conforming to IEC 60439-1
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 60439-1
[Ipk] rated peak withstand current	53 kA conforming to IEC 60439-1
Network frequency	50/60 Hz
Number of horizontal rows	2
Nb of modules	48
Additional information	3 divisible blanking plates An earth bar DIN rails for modular devices Front plates with cut-outs Plastic gland plate Top and bottom plain front plates
Height	480 mm
Width	550 mm
Depth	157 mm
Colour	White RAL 9001

Environment

IP degree of protection	IP30 with or without door
IK degree of protection	IK08 with door IK07 without door
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Standards	IEC 60439-1 IEC 62208

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.