



### Main

Range of product	Prisma Plus System G
Product or component type	Enclosure
Nb of modules	48
Additional information	3 divisible blanking plates An earth bar DIN rails for modular devices Front plates with cut-outs Plastic gland plate Top and bottom plain front plates

### Complementary

Installation description	Pack enclosure: 550 mm
[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 60439-1
[Ie] rated operational current	160 A at 40 °C conforming to IEC 60439-1
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 60439-1
[Ipk] rated peak withstand current	53 kA conforming to IEC 60439-1
Network frequency	50/60 Hz
Number of horizontal rows	4
Height	780 mm
Width	550 mm
Depth	157 mm
Colour	White RAL 9001

### Environment

IP degree of protection	IP30 with or without door
IK degree of protection	IK08 with door IK07 without door
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Standards	IEC 60439-1 IEC 62208

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0930 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Period	18 months
--------	-----------