



Main

Range of product	Prisma Plus System G
Product or component type	Enclosure
Nb of modules	48
Additional information	3 divisible blanking plates An earth bar DIN rails for modular devices Front plates with cut-outs Plastic gland plate Top and bottom plain front plates

Complementary

Installation description	Pack enclosure: 550 mm
[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 60439-1
[Ie] rated operational current	160 A at 40 °C conforming to IEC 60439-1
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 60439-1
[Ipk] rated peak withstand current	53 kA conforming to IEC 60439-1
Network frequency	50/60 Hz
Number of horizontal rows	5
Height	930 mm
Width	550 mm
Depth	157 mm
Colour	White RAL 9001

Environment

IP degree of protection	IP30 with or without door
IK degree of protection	IK08 with door IK07 without door
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Standards	IEC 60439-1 IEC 62208

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0930 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------