



Main

LV panel system name	Prisma Plus System G
Product or component type	Surface-mount Pack enclosure
Enclosure configuration	Base
Additional information	1 DIN rail for an NG160 at the top of the enclosure 1 DIN rail of 432 mm length with 4 raisers 1 bottom front plate with cut-outs 1 top front plate with cut-outs 6 divisible blanking plates DIN rails for modular devices An earth bar Front plates with cut-outs Plastic gland plate

Complementary

Dedicated enclosure type	Pack enclosure
Enclosure/Cubicle width	550 mm
Height	1080 mm
Depth	157 mm
[Ie] rated operational current	160 A
Number of horizontal rows	6
Nb of modules	48
Colour code	RAL 9001
Colour	White
Special colour options	Yes

Environment

IP degree of protection	IP30 with or without door
IK degree of protection	IK07 without door IK08 with door
Standards	IEC 60439-1
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
RoHS EUR conformity date	0930
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.