

Product datasheet

Specifications



Enclosure for modular device,
Mureva Enclosure, 2x18 modules,
earth and neutral terminal blocks

13434

⚠ Discontinued on: 14 Mar 2022

⚠ To be discontinued

Main

| | |
|----------------------------|------------------------------|
| Range | Mureva |
| Product Name | Mureva Enclosure |
| Product Or Component Type | Weatherproof enclosure |
| Enclosure Type | Enclosure for modular device |
| Mounting Plate Description | Without mounting plate |

Complementary

| | |
|---------------------------------|------------------------------------------------------------------------------------------|
| Enclosure Mounting | Surface |
| Number Of 18 Mm Modules Per Row | 18 |
| Total Number Of 18 Mm Modules | 36 |
| Number Of Horizontal Rows | 2 |
| Electrical Insulation Class | Double insulation Class II |
| Provided Equipment | 2 marking kit 2 wiring strap 1 terminal block support 2 terminal block 32 holes |
| Type Of Front Cover | Reversible Transparent |
| [In] Rated Current | 90 A |
| Type Of Rail | DIN |
| Number Of Pre-Cutouts Pg Iso | 17 |
| Number Of Terminal Blocks | 2 earth / neutral (screw connection) with 32 outgoers |
| Distribution Block Outgoers | 32 x 10 mm ² 32 x 16 mm ² |
| Locking Options Description | Optional keylock |
| Enclosure Material | Self-extinguishing polymer |
| Width | 448 mm |
| Height | 460 mm |
| Depth | 160 mm |
| Internal Depth | 88 mm |
| Colour | Door: transparent green Enclosure: light grey (RAL 7035) |

Environment

| | |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Standards | IEC 61439-3 EN 50262 IEC 60670 IEC 60695-2-1 |
| Fire Resistance | 650 °C conforming to IEC 60695-2-1 |
| Ip Degree Of Protection | IP65 conforming to IEC 60529 |
| Ik Degree Of Protection | IK09 conforming to EN 50102 |
| Environmental Characteristics (Uv) | UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage Category | II |
| Ambient Air Temperature For Operation | -25...60 °C |

Packing Units

| | |
|-------------------------------------|------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 17.500 cm |
| Package 1 Width | 47.000 cm |
| Package 1 Length | 47.000 cm |
| Package 1 Weight | 4.425 kg |
| Unit Type Of Package 2 | P12 |
| Number Of Units In Package 2 | 18 |
| Package 2 Height | 80.000 cm |
| Package 2 Width | 80.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 91.650 kg |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Lower Impact Materials Transparency RoHS/REACH

Resource performance

✓ Minimum Percentage Of Recycled Plastic Content 26

Well-being performance

✓ Rohs Exemption Information Yes

✓ Halogen Free Product

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations