



Main

| | |
|-------------------------------------|---|
| Range of product | TeSys D thermal overload relays |
| Product or component type | Differential thermal overload relay |
| Device short name | LRD |
| Relay application | Motor protection |
| Product compatibility | LC1D80 LC1D95 |
| Network type | AC DC |
| Overload tripping class | Class 10A conforming to IEC 60947-4-1 |
| Thermal protection adjustment range | 63...80 A |
| [Ui] rated insulation voltage | 600 V power circuit conforming to UL 600 V power circuit conforming to CSA 1000 V power circuit conforming to IEC 60947-4-1 |

Complementary

| | |
|--|---|
| Network frequency | 0...400 Hz |
| Mounting support | Under contactor |
| Tripping threshold | 1.14 +/- 0.06 I _r conforming to IEC 60947-4-1 |
| [I _{th}] conventional free air thermal current | 5 A for signalling circuit |
| Permissible current | 0.06 A at 440 V DC-13 for power circuit 0.72 A at 500 V AC-15 for power circuit |
| [U _e] rated operational voltage | 690 V |
| [U _{imp}] rated impulse withstand voltage | 6 kV |
| Phase failure sensitivity | Tripping current 130 % of I _r on two phase, the last one at 0 |
| Temperature compensation | -30...60 °C |
| Connections - terminals | Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - without cable end Power circuit: screw clamp terminals 1 cable(s) 4...35 mm ² - cable stiffness: solid - without cable end Power circuit: screw clamp terminals 1 cable(s) 4...35 mm ² - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 1 cable(s) 4...35 mm ² - cable stiffness: flexible - without cable end |
| Tightening torque | Power circuit: 9 N.m - on screw clamp terminals Control circuit: 1.7 N.m - on screw clamp terminals |
| Height | 123 mm |
| Width | 75 mm |
| Depth | 121 mm |
| Product weight | 0.51 kg |
| Quantity per set | Set of 10 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---|
| Standards | CSA C22-2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 |
| Product certifications | ATEX INERIS BV CCC CSA DNV GL GOST RINA UL LROS |
| Protective treatment | TH conforming to IEC 60068 |
| IP degree of protection | IP2x conforming to VDE 0106 |
| Ambient air temperature for operation | -20...60 °C without derating conforming to IEC 60947-4-1 |
| Ambient air temperature for storage | -60...70 °C |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Shocks 15 Gn for 11 ms IEC 60068-2-7 Vibrations 6 Gn IEC 60068-2-6 |
| Dielectric strength | 6 kV at 50 Hz conforming to 60255-5 |